



Potato Harvester Fully Autoamtic









Potato Harvester Fully Autoamtic



| Number of Rows | Single Row |
|---|---|
| Applicable Tractor Power | 35-50 HP |
| Productivity | 2.5 (acres/day) |
| Operating Speed | 2 - 3 (kmph @ 1500 ERPM) |
| Potato Coverage | 90% (> 30mm size) |
| Potato Damage | 3% |
| Drop Height | <300 (mm) |
| Manual Labor Requirement- Excluding Tractor Driver | <=4 |
| | |
| Flexibility to Accommodate Ridges - Centre to Centre Distance | 24, 26, 28, 30 inches |
| | 24, 26, 28, 30 inches <9 (m) |
| Centre to Centre Distance | 1901 B S |
| Centre to Centre Distance Turning Circle Diameter Along with Tractor | <9 (m) |
| Centre to Centre Distance Turning Circle Diameter Along with Tractor Collection Tank Capacity | <9 (m) 150 (kg) |
| Centre to Centre Distance Turning Circle Diameter Along with Tractor Collection Tank Capacity Dimensions | <9 (m) 150 (kg) 3.5 x 2.5 X 1.8 (l x w x h)(m) |
| Centre to Centre Distance Turning Circle Diameter Along with Tractor Collection Tank Capacity Dimensions Potato Cleaning Capability | <9 (m) 150 (kg) 3.5 x 2.5 X 1.8 (I x w x h)(m) 70-80% by weight |